

## MATERIAL SAFETY DATA SHEET

This substance is classified as **Hazardous** according to the criteria of Worksafe Australia

### ECO FREEZE OE AOC5005P LONG LIFE HYBRID (NITRITE) COOLANT - PREMIX

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

<b>Product Name</b>	ECO FREEZE OE Long Life Hybrid (Nitrite) Coolant - Premix
<b>Product Code</b>	AOC5005P
<b>Product Use</b>	Engine Cooling System Treatment
<b>Company Name</b>	Australian Organic Coolants
<b>Address</b>	110 Scott Street, Bungalow, Qld, 4870
<b>Telephone</b>	61 7 4051 2400
<b>Fax</b>	61 7 4031 5490
<b>Other Names</b>	
<b>Other Information</b>	

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Information on Composition	Chemical Entity	CAS number	Proportion
	Ethylene Glycol	107-21-1	30% - 60%
	Denatonium Benzoate	3437-33-6	<1%
	Other ingredients determined not to be hazardous		to 100%

#### 3. HAZARDS IDENTIFICATION

<b>Human Health Hazards</b>	<b>ACUTE</b>
<b>Eyes</b>	Can cause moderate irritation
<b>Skin</b>	Can cause moderate irritation
<b>Ingestion</b>	Harmful if swallowed. Large quantities may cause kidney damage. Irritation of the gastrointestinal tract may occur with nausea and vomiting.
<b>Inhalation</b>	Not a likely route of exposure. Mists or vapours may be irritating to eyes, nose throat and lungs.
<b>Human Health Hazards</b>	<b>CHRONIC</b>
	Contains mono ethylene glycol, which is toxic when swallowed. 100ml is considered a lethal dose for an adult. Repeated exposure to high doses by ingestion (animal studies) has caused kidney, liver and central nervous system damage.

#### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Wash eye thoroughly with copious quantities of water, ensuring eyelids are held open for at least 15 minutes. Obtain medical attention if irritation continues.
<b>Skin Contact</b>	Wash skin with soap and water as soon as reasonably practicable. Remove contaminated clothing. Seek medical attention.
<b>Ingestion</b>	If a significant quantity has been swallowed, do not induce vomiting. Give 2 glasses of water. Seek medical attention.
<b>Inhalation</b>	If inhalation of mists, fumes or vapour causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist obtain medical advice. As with any chemical, exposure by ingestion, inhalation or contact with eyes or skin should be avoided by correct occupational practices.
<b>Advice to Doctor</b>	Treatment should in general be symptomatic and directed to relieving any effects.

#### 5. FIRE FIGHTING MEASURES

<b>Flash Point</b>	Non flammable
<b>Extinguishing Media</b>	Choice of extinguishing media should be made by what other materials are present.
<b>Fire and Explosion Hazard</b>	Combustible – oxides of carbon may be evolved after evaporation of all the water.
<b>Special Protective Equipment for Fire Fighting</b>	In case of fire, wear a full face self-contained breathing apparatus and protective suit.



**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions</b>	Restrict access to area affected until clean-up is completed. Use personal protective equipment as detailed in section 8. Do not touch spilled material. Emergency equipment should be available. Notify appropriate authorities.
<b>Skin Environmental Precautions</b>	Do not contaminate surface waters – depletion of oxygen in the water will occur. Soak up spilled material using sand or other suitable inert absorbent material. Place residues in a suitably marked sealed container.
<b>Clean Up Methods</b>	Protect drains from potential spills to minimize contamination. In the case of large spills contact the appropriate authorities

**7. HANDLING AND STORAGE**

<b>Handling</b>	Use with adequate ventilation. Avoid contact with eyes. If splashing is likely to occur wear a full face visor or chemical goggles as appropriate.
<b>Storage</b>	Avoid frequent or prolonged skin contact. Wear PVC or similar gloves. Store only in original or approved containers. Store away from oxidizers.

**8. EXPOSURE CONTROLS, PERSONAL PROTECTION**

Occupational Exposure Limits	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	PEAK/CEILING ppm	PEAK/CEILING mg/m <sup>3</sup>
<b>Ingredient Name</b>				
Ethylene glycol (vapour)	60	120		
Ethylene glycol			50	125
<b>Engineering Measures</b>	Local exhaust ventilation should be provided.			
<b>Personal Protection</b>	Eyes Use chemical splash goggles.			
	Skin Wear standard protective clothing.			
	Hands Wear any impervious gloves.			
	Respiratory Respiratory protection is not generally needed. If ventilation is inadequate, use respirator that will protect against dusts and mists. Respiratory protection should confirm to AS/NZS 1715 & AS/NZS 1716.			

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Odour</b>	Slight
<b>Boiling Point</b>	N/A
<b>PH Value</b>	8.1 – 8.3
<b>Vapour Pressure</b>	N/A
<b>Physical State</b>	Liquid
<b>Colour</b>	Pale Green
<b>Density</b>	1.121 – 1.123

**10. STABILITY AND REACTIVITY**

<b>Hazardous Polymerisation</b>	Hazardous polymerization reactions will not occur.
<b>Materials to Avoid</b>	Strong oxidizers
<b>Hazardous Decomposition Product</b>	Oxides of carbon
<b>Conditions to Avoid</b>	Products of this type are stable and unlikely to react in a hazardous manner under normal conditions of use. This material is combustible after evaporation of the aqueous component.



## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY DATA

The following results are for Ethylene Glycol.

Acute Oral Toxicity	LD50 (Rat) 4700mg/kg Lowest lethal dose (human) 786mg/kg Estimated lethal dose (human) 100ml
Acute Dermal Toxicity	LD50 (Rabbit) 9350mg/kg
Acute Inhalation Toxicity	(Rat) >5mg/kg

### SENSITIZATION

This product is not expected to be a sensitizer.

### CHRONIC TOXICITY

Contains ethylene glycol. Repeated high ingested doses of ethylene glycol in animal studies brain damage, kidney damage, degeneration of the liver and changes in blood chemistry. Similar effects may be caused in humans by repeated and/or prolonged exposure.

### CARCINOGENICITY

This product does not contain any substances that are listed as carcinogens.

### TERATOGENICITY

Ethylene glycol has been shown to produce teratogenic effects in mice when high doses were ingested.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	No ecotoxicity studies have been done on this product. Ethylene glycol is classified as "readily" biodegradable according to the guidelines of the OECD.
<b>Mobility</b>	Not determined.
<b>Bioaccumulation</b>	Ethylene glycol does not bioaccumulate.

## 13. DISPOSAL CONSIDERATIONS

Dispose of via an authorized person/licensed waste disposal contractor in accordance with local regulations.  
Dispose of product and container carefully and responsibly.  
Do not dispose of near ponds, ditches, down drains or onto soil.

## 14. TRANSPORT INFORMATION

<b>UN Number</b>	Not classified as a dangerous good according to the criteria of the ADG Code.
<b>Proper Shipping Name</b>	None allocated
<b>DG Class</b>	None allocated
<b>Hazchem Code</b>	C1 – Combustible Liquid
<b>Packing Group</b>	None allocated

## 15. REGULATORY INFORMATION

<b>POISON SCHEDULE</b>	<b>5</b>
Hazardous according to the criteria of the	National Health and Occupational Health and Safety Commission
<b>Classification</b>	Xn – harmful
<b>Risk Phrases</b>	R36/37/38 irritating to eyes, respiratory system and skin
<b>Safety Phrases</b>	S2 KEEP OUT OF REACH OF CHILDREN S24/25 avoid contact with skin and eyes S37/39 wear suitable gloves and eye protection S45 in case of accident or if you feel unwell, seek medical advice immediately.

## 16. OTHER INFORMATION

<b>Important Information</b>	This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Australian Organic Coolants. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.
------------------------------	---

<b>Contact Point</b>	<b>Peter Heath</b> <b>Director</b> <b>Tel No: 61 7 40512400</b> <b>Fax No: 61 7 40315490</b>
----------------------	---

**END OF MSDS**

